

TANIX

professional signage solutions
www.tanix.be

30 W LED FLOOD LIGHT

Inpmut Voltage	AC85V ~ 265V	
Frequency Range	50Hz ~ 60Hz	
Total harmonic Distortion	≤ 9%	
Power Factor	> 0.98	
Power efficiency	> 82%	
LED Working Voltage	DC30 ~ 36V	
LED	1 piece	
LED Consumption	25 W	
System Consumption	30 W	
LED Luminous Efficiency	60 ~ 100 Lm / W	
Initial flux	WW	1944 Lm
	PW	2069 Lm
	CW	1986 Lm
Lamp's Efficiency	> 85%	
Average Illuminance	2 m	26 Lux
	3 m	11.5 Lux
	4 m	6.5 Lux
Illuminance Area	2 m	3.3 x 3.3 m
	3 m	6.5 x 6.5 m
	4 m	9.8 x 9.8 m
Illuminance Uniformity	> 0.6	
Color Temperature	WW	2700°K ~ 3900°K
	PW	3900°K ~ 6000°K
	CW	6000°K ~ 7000°K
Color Rendering Index	WW	Ra > 68
	PW	Ra > 75
	CW	Ra > 75
Junction Temperature	≤ 80° C	
Working Temperature	-40° C ~ +55° C	
Storage Temperature	-25° C ~ +65° C	
IP Grade	IP65	
Working Life Span	50.000 H	
Power Line	0.75 mm ²	
	Brown	L
Connect Wire	Blue	N
	Yellow/Green	G

